# GSS9000 Series

The very best in performance, flexibility and capability for GNSS developers and testers

**Datasheet with Product Specification**

# Spirent **GSS9000 Series GNSS Simulation System**

## Purpose of this Document

This datasheet describes the functionality of the Spirent GSS9000 Multi-Frequency, Multi-GNSS RF Constellation Simulator, which sets a new standard of excellence in GNSS RF Simulation for R&D and performance test.

This datasheet also provides technical data and configuration information.

**The GSS9000 offers a very wide range of capabilities and options. Please speak to your Spirent sales representative before ordering to ensure your specific needs are met.**

**PROPRIETARY INFORMATION**

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF SPIRENT COMMUNICATIONS PLC. EXCEPT AS SPECIFICALLY AUTHORISED IN WRITING BY SPIRENT COMMUNICATIONS PLC, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES TO THE SAME DEGREE IT PROTECTS ITS OWN CONFIDENTIAL INFORMATION.

© COPYRIGHT SPIRENT COMMUNICATIONS PLC 2019 - 2020

The ownership of all other registered trademarks used in this document is duly acknowledged.

# Table of Contents


Purpose of this Document ..... 2
Table of Contents ..... 3
List of Tables ..... 4
List of Figures ..... 4
Introduction ..... 5
Ultimate Flexibility, Supreme Performance, Comprehensive Capability ..... 5
SimGEN™ Scenario Definition and Simulation Control Software ..... 6
Extensions and Options ..... 7
GSS9000 Feature / Capability Temporary Licensing ..... 7
GSS9000 System Overview ..... 8
GSS9000 Signal Generator Chassis ..... 8
GSS9000 C50r SimGEN Host ..... 8
GNSS Constellations ..... 9
GPS Simulation ..... 11
SBAS Simulation ..... 11
Galileo Simulation ..... 12
GLONASS simulation ..... 12
BeiDou simulation ..... 12
Quasi-Zenith (QZSS) Simulation ..... 13
NavIC (IRNSS) Simulation ..... 13
FLEX Simulation ..... 13
Authorised Testing ..... 14
GPS authorised testing ..... 14
Galileo authorised testing ..... 14
FPGA Module daughter card ..... 14
Embedded Multipath Simulation ..... 15
Multi-Chassis capability ..... 15
Tailored Multi-output capability ..... 15
Ancillary Components ..... 16
Upgrades ..... 16
Calibration status ..... 16
Example composite output GSS9000 systems ..... 17
Optional single-RF combination in a dual-RF system ..... 19
Detailed Performance Specifications ..... 20
Performance in multi-chassis configurations ..... 26
Related Brochures, Data Sheets and Specifications ..... 29
ICD Compliance – Applicable Documents ..... 30
Glossary of terms ..... 31
For more information ..... 32

# Spirent **GSS9000 Series GNSS Simulation System**

## List of Tables

Table 1 Supported variations for each channel bank ....9
Table 2 GPS Signals ....11
Table 3 SBAS Signals ....11
Table 4 Galileo Signals....12
Table 5 GLONASS Signals....12
Table 6 BeiDou Signals ....12
Table 7 QZSS Signals ....13
Table 8 FLEX Simulation ....13
Table 8 Nominal Signal Levels ....20
Table 9 Navigation Messages Types per Constellation ....21
Table 10 FLEX Option Signal Definitions ....22
Table 11 Performance Levels for GSS9000 Series....22
Table 12 GTx Performance ....23
Table 13 Signal Generator Connectivity....27
Table 14 C50r SimGEN Host Connectivity....27
Table 15 Physical and Environmental Properties....28
Table 16 Safety and EMC Compliance ....28
Table 17 Related Product References ....29
Table 18 ICD compliance (WORK IN PROGRESS)....30

## List of Figures

Figure 1 SimGEN scenario definition and simulation control software....6
Figure 2 GSS9000 system....8
Figure 3 GSS9000 Signal Generator Chassis RF Channel Bank configuration (Single and dual composite output variants shown)....10
Figure 4 Example of a single output, 2-bank system GPS L1 L2....17
Figure 5 Example of a single output, 3-bank system....18
Figure 6 Example of a dual-RF Output, 6-bank system ....18
Figure 7 Example of a dual-RF output, 10-bank, 320-channel system ....19

## Introduction

To develop positioning, navigation and timing systems for military, space, and other high precision applications you require comprehensive, highly sophisticated testing. The updated GSS9000 Series multi-frequency, multi-GNSS RF constellation simulator sets a new standard of excellence in future-proofed simulation for R&D and performance testing.

Powered by SimGEN®, and using the latest state-of-the-art technology designed specifically for GNSS signal simulation, the GSS9000 Series produces a comprehensive range of emulated RF signals with industry-leading flexibility, fidelity, performance and reliability.

## Ultimate Flexibility, Supreme Performance, Comprehensive Capability

The GSS9000 supports an extensive range of constellation configurations, from GPS L1 C/A through to multi-GNSS, multi-frequency systems including authorised signals. Configurations are available that support multi-antennas and multi-vehicles, for example differential-GNSS, attitude determination, interference/jamming and spoofing and Controlled Reception Pattern Antenna (CRPA) testing.

Some of the GSS9000's key attributes are:

- World-leading performance in several key areas such as:
  - 1000 Hz System Iteration Rate (SIR) and Hardware Update Rate (HUR)
  - 0.3 mm RMS Pseudorange Accuracy
  - 0 mm uncertainty due to inter-channel bias
  - <0.005 Rad RMS Phase Noise
- Highly flexible configurations selectable via a 'cabinet' of feature licence keys
- Complete portability of Spirent SimGEN™ scenarios
- In-field upgradeability of principal GNSS functionality and capability
- On-the-fly re-configuration of constellation and signal configurations
- All GNSS constellation types and all frequencies brought into a single chassis
- Multi-RF output options available
- Embedded Interference Sources option (GTx) available
- Backward compatibility with legacy scenarios enabling seamless transition from existing Spirent platforms
- Fully future-proofed for all advances in GNSS systems, signals, modulations, codes and data

**A key benefit of the GSS9000 is that the signal performance specification is met under ALL operating conditions, including the full range of ultra-high dynamics.**

In view of the wide range of possible permutations, Spirent recommends that you discuss your current and future needs with your local sales representative. Spirent will provide specific configuration and pricing information to meet your needs.

# Spirent **GSS9000 Series GNSS Simulation System**

## SimGEN™ Scenario Definition and Simulation Control Software

SimGEN™ is Spirent's software application suite that supports the GSS9000.

SimGEN™ is the world's leading GNSS simulation software for test scenario definition, execution, data management and GNSS RF constellation simulator command and control. With the fullest capability, features and performance continuously developed in close consultation with GNSS system authorities over more than 30 years, SimGEN™ supports all the GNSS test parameters and control capabilities needed for comprehensive GNSS testing for research, development and design of GNSS systems, services and devices across any application.




**Figure 1 SimGEN scenario definition and simulation control software**

Some of SimGEN's fundamental performance and modelling capabilities include:

- Fully automatic and propagated generation of precise satellite orbital data, ephemerides and almanac
- Multiplicity of mechanisms for applying declared and undeclared errors and modifications to navigation data, Satellite clocks and orbits
- SimREMOTE: Comprehensive simulation control and 6-DOF trajectory delivery capability
- Data logging and streaming of signal, time, control, vehicle and trajectory data over a variety of interfaces in real-time and to file
- Range of models for Multipath reflections
- Terrain obscuration models
- Independent satellite/channel signal power control
- Signal modulation and code control
- Multi-copy constellations for spoofing testing
- 2-vehicles to 1RF for trajectory spoofing
- Vehicle personalities and motion modelling for aircraft, spacecraft, marine vessels and land vehicles
- Antenna reception gain and phase patterns

- Satellite transmit antenna pattern control
- Clock g-sensitivity
- Antenna lever arm effects
- INS aiding data
- Ionosphere and Troposphere effects including ionospheric scintillation
- DGPS corrections
- Pseudorange ramps (for RAIM testing)
- Coherent and non-coherent Interference and noise modelling (with optional GSS7765 Interference Simulation System)
- Leap-second and week roll-over event testing

More information about the capabilities of SimGEN™ can be found in the separate specification document, see Table 18.

## Extensions and Options

Extensions and options are available with the GSS9000 to facilitate development and testing of systems and applications which use other GNSS codes/signals and alternative technology for position, navigation and time determination alongside GNSS. These include:

- Authorised GPS and Galileo signal generation for authorised users (see 'Authorised Testing' section)
- GBAS VHF Data Broadcast Simulation available with the GSS4150 solution.
- Inertial Test input simulation of several types of Integrated GPS/Inertial (IGI) navigation sensors (also known as EGIs) and emulation of the presence of Inertial Measurement Units (IMU) with SimINERTIAL™ and SimAUTO™
- Interference signal generation, using the GSS7765™ Interference Simulation System, where the interference sources are positioned and dynamically modelled by the GSS9000 system
- Embedded in-band interference (Ground Transmitters – GTx) With a variety of modulations and signal controls (See Table 13)
- Sophisticated jamming laboratory testing using the GSS7765 Interference Simulation System and spoofing laboratory testing using Spirent's SimSAFE™ solution alongside in-built capabilities

## GSS9000 Feature / Capability Temporary Licensing

The flexibility of the GSS9000 allows constellations and channels to be temporarily enabled on a time-limited rental basis. This is particularly useful if the system is to be used for short to medium-term projects requiring an additional constellations and/or additional satellite channels for a defined period. An existing GSS9000 system can have additional feature(s) enabled by providing the user with a suitably revised soft licence key, the intention is that a system is returned to a default condition upon expiry of the temporary licence. If licences are consecutively renewed for the requisite number of times, the feature becomes permanent and the licence runs in perpetuity.

# Spirent **GSS9000 Series GNSS Simulation System**

## GSS9000 System Overview

The GSS9000 system consists of a Signal Generator Chassis and dedicated C50r Host Unit running Spirent's SimGEN™ scenario definition and simulation control software, as shown in Figure 2.

**Figure 2 GSS9000 system**

## GSS9000 Signal Generator Chassis

The GSS9000 Signal Generator Chassis consists of one or more **RF Channel Banks**. An RF Channel Bank consists of 2 cards - a digital signal generator card and an RF up-converter card. Each RF Channel Bank is licenced to support; **4, 8, 12, 16 or 32 separate channels**. Each RF Channel Bank is capable – at any one time – of supporting any number of licenced GNSS constellations in the same frequency band.

The Signal Generator Chassis is available in 2 main variants:

- Single RF Output - behind which up to 10 RF Channel Banks can be installed
- Dual RF Output - with up to 5 RF Channel Banks installed behind RF Output 1 and up to 5 RF Channel Banks installed behind RF Output 2.
    - Optionally, the Dual RF Signal Generator Chassis can be provided with the capability for the RF Channel Banks behind RF Output 2 to be configured to operate as interference sources (GTx – Ground Transmitters), using a dedicated rear panel link cable.
    - There are also multi-output versions of the 1-RF and 2-RF chassis (supported as Tailored Solutions), allowing highly flexible configurations to be tailored to specific needs, such as the GSS9790 CRPA/Wavefront system.

This extensive capacity enables a single Signal Generator Chassis to support up to **320 independent channels**. In addition to this, each primary channel also supports an additional **4 embedded multipath channels** that are delayed and attenuated copies of the primary channel and are applied to the first 16 channels of the bank, giving up to **640 embedded multipath channels** in a single chassis..

## GSS9000 C50r SimGEN Host

The Signal Generator Chassis is controlled by a dedicated, rack-mountable **C50r SimGEN Host**, which is a Spirent proprietary design, multi-processor/core system, configured with a mixed Operating System (OS) environment (Linux and Windows® 10 Professional for Embedded Systems ESD [Virtualisation Only]) This combination of processing power and dual OS provides the perfect platform to enable the GSS9000's new bench-mark performance levels, and to support Spirent's SimGEN™ scenario definition and simulation control software application. The C50r SimGEN Host is supplied with a free-standing monitor, desktop keyboard and mouse.

## GNSS Constellations

The GSS9000 architecture supports GNSS signal generation capability in a very flexible way. With the appropriate constellation feature licence keys, each generic RF Channel Bank can support **– at any one time –** any one of the constellation/frequency variations as shown in Table 1 (for current ICD compliance, see Table 19).

The combinations of constellations generated can vary from scenario to scenario and even between successive runs of the same scenario, depending on the settings in SimGEN. The principle is that at an instant in time, signals from any constellation can be generated provided there is a valid feature licence key and an available RF Channel Bank in the system.

**Table 1 Supported variations for each channel bank**

| Variation | Constellation | Frequency |
|---|---|---|
| 1 | GPS/SBAS | L1 |
| 2 | GPS | L2 |
| 3 | GPS/SBAS | L5 |
| 4 | Galileo | E1 |
| 5 | Galileo | E5 |
| 6 | Galileo | E6 |
| 7 | GLONASS | L1 |
| 8 | GLONASS | L2 |
| 9 | BeiDou | B1I |
| 10 | BeiDou | B2I |
| 11 | BeiDou | B1C |
| 12 | BeiDou | B2A |
| 13 | BeiDou | B3I |
| 14 | SBAS (note 1) | L1 |
| 15 | SBAS (note 1) | L5 |
| 16 | QZSS | L1 |
| 17 | QZSS | L2 |
| 18 | QZSS | L5 |
| 19 | QZSS | L6 |
| 20 | NavIC (IRNSS) | L5 |
| 21 | Others (note 2) | - |

Notes for Table 1

1. In addition to the support of GPS-based SBAS augmentations (WAAS, EGNOS, MSAS, GAGAN) and SDCM on any dedicated GPS channel bank, it is possible to have a channel bank solely generating SBAS augmentations

2. The GSS9000 is technology-ready for support of other future GNSS systems/signals, some of which can be supported today as Tailored Solutions, and some of which are planned on the current product roadmap. Please contact Spirent for further information if you have a requirement for capability not explicitly detailed in this specification.

# Spirent **GSS9000 Series GNSS Simulation System**

Figure 3 illustrates the feature licence key/generic RF Channel Bank architecture of the GSS9000:




**Figure 3 GSS9000 Signal Generator Chassis RF Channel Bank configuration (Single and dual composite output variants shown)**

## GPS Simulation

The supported ranging signal types of the GPS constellation are shown in Table 2

**Table 2 GPS Signals**

| Carrier | Standard Signal Types | Optional Signal Types | Notes |
|---|---|---|---|
| L1 | C/A, L1c Data/Pilot, P, M Noise, Pseudo Y | Y, MNSA-M, AES-M and SDS-M-Code via data server, GTx | "Pseudo-Y" code is generated through public-domain encryption of P-code to fully support L1/L2 squaring or 'Z-tracking', with data message.<br>"M Noise" is a spectrally representative M-Code signal from each satellite when enabled, with no data message.<br>See 'Authorised Testing' section for information on optionally available GPS authorised signals. |
| L2 | L2c, P, Pseudo Y, M Noise | Y, MNSA-M, AES-M and SDS-M-Code via data server, GTx | C/A code is also supported as on this carrier as an alternative to L2c.<br>See 'Authorised Testing' section for information on optionally available GPS authorised signals. |
| L5 | I, Q | N/A | N/A |

## SBAS Simulation

SBAS (defined as WAAS, EGNOS, MSAS, SDCM and GAGAN) simulation capability is included with GPS configurations at L1 and/or L5. Note that SBAS uses available GPS channels when choosing channel count for GPS L1 and L5.
In addition, a separate SBAS licence key can be purchased which allows SBAS to be run on a separate RF Channel Bank, without the need to 'use up' GPS L1 or L5 channels.

The supported ranging signal types of the SBAS constellation are shown in Table 3

**Table 3 SBAS Signals**

| Carrier | Standard Signal Types |
|---|---|
| L1 | C/A |
| L5 | I |

# Spirent **GSS9000 Series GNSS Simulation System**

## Galileo Simulation

The supported ranging signal types of the Galileo constellation are shown in Table 4.

**Table 4 Galileo Signals**

| Carrier | Standard Signal Types | Optional Signal Types | Notes |
|---|---|---|---|
| E1 | PRS Noise, OS Data/Pilot | PRS via 'PRS[WARE]' | See Authorised Testing for information on Galileo authorised signals |
| E6 | PRS Noise, CS Data/Pilot (without encryption) | PRS via 'PRS[WARE], CS Data/Pilot (with encryption) | See Authorised Testing for information on Galileo authorised signals |
| E5ab | E5a Data/Pilot, E5b Data/Pilot | N/A | E5ab signalling employs 8-PSK modulation of E5a and E5b onto a single carrier. Appropriate carrier dispersion is applied from E5a to E5b |

Galileo Open Service (OS) ICD support is supplied as standard. Optional support for Galileo Full Operational Capability (FOC) signalling is available with Spirent's **SimCS™** option, subject to user status.

Galileo PRN data is available form a user definable file. Open Service users are supplied with PRN data for the E1B/C and E5a signal components, PRN data for other signal types is 'dummy data'.

FOC authorised users are supplied with PRN data signal for all signal types, except for PRS.

PRS requires the third-party extension **PRS[WARE]** upgrade, see Authorised Testing..

## GLONASS simulation

The supported ranging signal types of the GLONASS constellation are shown in Table 5

**Table 5 GLONASS Signals**

| Carrier | Signal types |
|---|---|
| L1 | C/A, P (Chan Number -7 to +6) |
| L2 | C/A, P (Chan Number -7 to +6) |

GLONASS is supported in accordance with the SISICD GLONASS Interface Control Document, see Table 19.

## BeiDou simulation

The supported ranging signal types of the BeiDou constellation are shown in Table 6

**Table 6 BeiDou Signals**

| Carrier | Signal types |
|---|---|
| B1 (1.561098 GHz) | B1I |
| B1 (1.57542 GHz) | B1C |
| B2 (1.20714 GHz) | B2I |
| B2 (1.17645 GHz) | B2A |
| B3 (1.26852 GHz) | B3I |

BeiDou Phase-2 is supported in accordance with the BeiDou-2 Open Service SIS ICD, see Table 19. Spirent's implementation includes the B1I signal described in the SIS ICD and offers the same signalling on the B2I frequency. D1 and D2 navigation data supports the provision of full Ephemerides and Almanacs as well as system time offsets. As an interim solution,

As at this issue, BeiDou Phase-3 is supported in accordance with Beidou3_ICD_B1C_B2a Beta version, 2017-08. Customers purchasing BeiDou Phase-3 licence keys for B1C and/or B2A will receive a FOC software upgrade when the implementation to BDS-SIS-ICD-B1C/B2A-1.0 2017-12 is completed. Spirent plans to complete this implementation by end Q3-2018

## Quasi-Zenith (QZSS) Simulation

The supported ranging signal types of the Quasi-Zenith constellation are shown in Table 7

**Table 7 QZSS Signals**

| Carrier | Signal types |
|---|---|
| L1 | SAIF, C/A, L1c |
| L2 | L2c |
| L5 | I, Q |
| L6 | L61/L62 (Available Q4 2018) |

QZSS is supported in accordance with the QZSS Interface Specifications in Table 19.

## NavIC (IRNSS) Simulation

The supported ranging signal types of the Quasi-Zenith constellation are shown in

| Carrier | Signal types |
|---|---|
| L5 | C/A |
| S | Available as a Tailored Solution only – please contact Spirent |

NavIC is supported in accordance with the IRNSS_SPS_ICD see Table 19

## FLEX Simulation

FLEX simulation comprises built-in and user-configurable control and set-up of non-current SIS ICD PRN codes, nav data content, nav data rate, chipping rate, edge shaping, and modulation types.

**Table 8 FLEX Simulation**

| Carrier | Signal types |
|---|---|
| L1,L2,L5,E1,E5,E6, B1,B2,QZL1 | User-definable codes – See Table 11 |

Three user-definable codes are supported per FLEX channel which corresponds to a single simulated SV. The Galileo E5 AltBOC signal structure is not supported on FLEX channels.

# Spirent **GSS9000 Series GNSS Simulation System**

## Authorised Testing

### *GPS authorised testing*

GPS authorised testing is supported via a range of additional options (see Related Brochures, Data Sheets and Specifications referenced within this datasheet specification). **In all cases, the options are available for authorised users only.**

Selective Availability/Anti-Spoofing (SA/A-S) simulation is available for GSS9000 as an option. The applicable package is **SimSAAS** (for customers in USA) or **SimCLASS** (non-US). These options add additional capabilities - that includes SA/A-S simulation - to standard GSS9000 systems.

Standard product broadcasts a spectrally representative “M-Noise” signal from each satellite when enabled, with no data message.

MNSA M-Code requires the **SimMNSA** option which is available for US authorised users only

AES M-Code requires the **SimMCODE** option – available subject to end-user approval by US authorities.

SDS-M-Code requires the **SimMCODE and SDS-M-Code via data server** option – available subject to end-user approval. Note: SDS-M-Code via data server option is not a customer in-field upgrade.

Further detail is given in Detailed Performance Specifications.

### *Galileo authorised testing*

Galileo FOC authorised testing can be supported with the Public Regulated Signal (PRS) at E1 and E6 and the encrypted part of the Commercial Service (CS) at E6. Full PRS requires the **PRS[WARE] upgrade** option. Full CS requires the **SimCS upgrade** option, (which also enables Safety-of-Life at E5) Both PRS[WARE] and SimCS provide the required full PRN data for the respective signals they support (non-authorised users are only supplied with ‘dummy’ data for these signals).

In all cases, the options are available for authorised users only.

The way PRS is supplied for the GSS9000 has changed. Order processing for the new “PRS[WARE]” solution is entirely managed by LZE GmbH of Erlangen, Germany, with Munich-based Fraunhofer IIS having complete responsibility for the current and future development, fulfilment and support of PRS[WARE] operating on the Spirent GSS9000 and future Spirent GNSS test solutions.

Fraunhofer IIS is the sole owner of PRS[WARE] software/firmware, therefore, all issues and questions relating to PRS and PRS[WARE] must be directed to Fraunhofer IIS

Spirent cannot provide any support relating to PRS, please contact LZE and Fraunhofer IIS directly for all questions relating to the PRS capability and ordering

LZE can be contacted as follows:

LZE GmbH, Tel: +49 9131 92894-85, contact@prs-ware.de

### *FPGA Module daughter card*

A dedicated FPGA Module daughter card has been developed to work in unison with each signal generator RF Channel Bank and associated software modules to support authorised testing. The FPGA Modules are designed to enable:

- **GPS**: - Y code SA/A-S* with SimCLASS* or SimSAAS (US–only) software, MNSA M-code with SimMNSA, AES-M-code with SimMCODE software and SDS M-Code via data server with an extension to SimMCODE
- **Galileo**: - PRS with PRS[WARE] software, and/or Galileo FOC with SimCS for approved users.

*The procurement and supply of FPGA Modules specifically for GPS SA/A-S (for **Non-US** customers) involves a customer’s government to US government Foreign Military Sales (FMS) procurement process.

**This process can be lengthy, so customers are strongly advised to discuss their requirements with Spirent and contact the appropriate department within their government at the earliest opportunity.**

Supply of FPGA Modules for AES-M-code with SimMCODE are not subject to an FMS process.

## Embedded Multipath Simulation

The GSS9000 can generate up to 4 multipath channels per satellite signal source. These multipath channels are delayed and attenuated copies of the primary channel and are applied to the first 16 channels in each channel bank. The delay and attenuation of each path is user-specified and fixed for the simulation duration of that satellite. This gives up to **640 Multipath** channels in one GSS9000 Signal Generator Chassis (i.e. 10 channel banks x 16 channels per channel bank x 4 embedded multipath channels).

The embedded multipath simulation capability is in addition to the comprehensive multipath modelling supported by SimGEN™ that uses spare generator channels, see Table 18. The comprehensive multipath modelling provides full control of multipath signals, including nav data, e.g. for advanced spoofing attack vectors simulation, using independent hardware channels, up to the licensed allowance.

## Multi-Chassis capability

The GSS9000 system can be configured to include up to 4 Signal Generator Chassis' controlled as a coherent system via a single C50r and one SimGEN scenario. Applications for this configuration include multiple GNSS antenna simulation where composite, multi-GNSS signals are required on each antenna, and/or an increase in the number of simulated satellites beyond the 320 supported in a single chassis. For GSS9000 systems consisting of greater than two chassis, a GSS9367 Distribution Unit is required for management and distribution of various signals.

Spirent can provide equipment rack solutions to house GSS9000 systems consisting of multiple components.

Please note that the performance of GSS9000 in multi-chassis configurations can vary depending on several factors. Please refer to the Detailed Performance Specifications section for more information

## Tailored Multi-output capability

The GSS9000 architecture supports the provision of a multiple-RF output capability where the signal on each channel bank can be output via a dedicated 'N-type- RF connector on the front panel. This provides significant flexibility in support of various multi-antenna and/or multi-vehicle test configurations.

Also available is a variant called GSS9790 which has been specifically developed to provide the core element in GNSS test applications that require independent access to each simulated satellite signal at RF. Up to 10 independent signal output ports, each with its own dedicated baseband signal generator channel and RF up-converter are provided.

These multi-output RF options are supplied as Tailored Solutions only. Applications include:

- **CRPA - Control unit testing**. The system can be integrated with a user-supplied multi-element RF phase shift or delay matrix to produce an RF wave-front at multiple simulated antenna elements.
- **CRPA - System Testing**. The system can be used as the signal generator attached to multiple transmission antennas installed in an anechoic chamber. The antennas are spatially distributed to present the appropriate arrival vectors of the simulated satellite signals at the antenna site. Interference sources can then be located anywhere in the chamber to represent different test cases. This is the only possible alternative to live testing of a complete CRPA system, including the actual antenna. By mounting the antenna on a rate table that replicates the attitude changes of the simulated vehicle platform comprehensive evaluation of all aspects of the CRPA system can be achieved in a secure environment, free from unintentional interference, both incoming and outgoing, and free from external observation.
- **Radiated Testing**. Again, using an anechoic chamber with radiating antennas, the system can provide spatial signal diversity for testing items such as GPS-equipped mobile telephones

# Spirent **GSS9000 Series GNSS Simulation System**

and PDAs through the actual antenna. Items such as reflectors, signal attenuators (a dummy human head for example) can be physically placed adjacent to the unit under test to emulate environments.

- **Indoor GPS**. With appropriate real-world time synchronisation and transmission antennas, the system can form the basis of an experimental indoor GPS implementation.

If you are interested in GSS9000 multi-output capabilities, please contact Spirent to discuss your requirements.

## Ancillary Components

Depending on the system configuration, ancillary components may be required to distribute, synchronise and combine signals from more than one chassis. These include a Signal Distribution Unit (for systems with more than two chassis) and a Multi-chassis Combiner Unit. If these elements are required for your system configuration these will be detailed on the quotation.

### *Upgrades*

The extensibility of the GSS9000 means that **in-field upgrading** of the system can be achieved easily, flexibly and in a way which matches the developing needs of your testing requirements as closely as possible.

- Existing RF Channel Banks can be issued with new licence keys, allowing extra channels to be added
- Additional constellation licences can be added allowing other signal types to be enabled
- New RF Channel Banks can be added to enable signal types using existing feature keys
- Both RF Channel Banks and new feature keys can be added in the field. It is not necessary for the system to be returned to Spirent

This extensibility makes the GSS9000 very flexible in terms of future-upgradeability.

Additional upgrade options are listed in the Related Product References, see Table 18. Please contact Spirent to discuss your requirements.

## Calibration status

Spirent Positioning Technology calibrate the GSS9000 simulator to the ISO/IEC 17025 standard. This Accredited Calibration comes with a default 12-month calibration period.

Annual re-calibration must be carried out at a Spirent facility or accredited laboratory to maintain this accreditation.

Please note that installation of additional purchased channel banks or performing calibrations outside of a Spirent authorized ISO/IEC17025 accredited laboratory will invalidate this accredited calibration.

This includes customer use of the Auto Calibration Utility (where installed) and certain upgrade procedures. Customers are advised to refer to procedural documentation for further details.

For more information on Spirent's calibration service, customers may refer to MS3089: Spirent Support Service for Positioning Technology Products, Customers who require more information on how to renew the annual accredited calibration, may contact their local Spirent representative.

## Example composite output GSS9000 systems

Given the highly flexible architecture of the GSS9000, many different system configurations are possible. Some systems may have the required number of RF Channel Banks to support simultaneous generation of all licenced signals, some systems may have more licenced signals than RF Channel Banks to support them, and so different combinations of signals are possible.

This section shows just a few examples of the extensive number of possible combinations and modes of operation. Your Spirent representative will be pleased to guide you through the process of selecting the best configuration for you current and future test requirements.

In the configuration shown in Figure 4, there is a single-RF output chassis with two RF Channel Banks, 64 channels, a feature licence key for GPS/SBAS L1, plus a feature licence key for GPS L2. The system can therefore generate all the licenced signals simultaneously.




**Figure 4 Example of a single output, 2-bank system GPS L1 L2**

In the configuration shown in Figure 5, there are three RF Channel Banks and 6 feature licence keys.

There is a single-RF output chassis with three RF Channel Banks, 96 channels, a feature licence key for GPS/SBAS L1, GLONASS L1, Galileo E1, BeiDou B1, GPS L5 an Galileo E5 plus a feature licence key for GPS L2. The system can therefore generate signals for all the licenced constellations simultaneously.

# Spirent **GSS9000 Series GNSS Simulation System**




**Figure 5 Example of a single output, 3-bank system**

In the configuration shown in Figure 6, there are 2 RF outputs, allowing signals for either one vehicle with two independent antennas or, two independent vehicles with one antenna each, to be simulated.

The configuration has three RF Channel Banks per RF output (so 6 in total) and two feature keys for each of the desired constellations (GPS and GLONASS). Therefore, the system can generate the licenced signals simultaneously on both outputs.




**Figure 6 Example of a dual-RF Output, 6-bank system**

In the configuration shown in Figure 7, there are two RF outputs, allowing signals for either one vehicle with two independent antennas or, two independent vehicles with one antenna each, to be simulated.

The configuration has five RF Channel Banks per RF output (so 10 in total), 320 channels and two feature keys for each of the desired constellations (GPS, GLONASS, Galileo, Beidou and NavIC). Therefore, the system can generate the licenced signals simultaneously on both outputs.




**Figure 7 Example of a dual-RF output, 10-bank, 320-channel system**

## Optional single-RF combination in a dual-RF system

With a dual-RF GSS9000 system it is possible to generate Differential-GNSS signals for GNSS signal types simultaneously, as each RF Output can have up to five RF Channel Banks behind it. However, for some tests, the user may wish to have all GNSS signal types from just one RF output.

To support this, an RF Link Cable is provided free-of-charge, for use with dual-RF Signal Generator Chassis.

When required, the RF Link cable is fitted to the rear of the Signal Generator Chassis and it combines all the signals associated with RF#2 with those of RF#1 and outputs them all at RF 1. The RF Link Cable can only be used on signal generator chassis without the front-panel high-level ports option fitted, and the use of the cable prevents access to the high-level port for RF#1 on the rear panel. .

SimGEN allows the user to select an operating mode which compensates for power level and group delay of the re-routed signal path.

# Spirent **GSS9000 Series GNSS Simulation System**

## Detailed Performance Specifications

**Table 9 Nominal Signal Levels[1]**

| System | Carrier | Signal | Level |
|---|---|---|---|
| GPS | L1 | C/A | -130.0 dBm |
| | | L1c Pilot code | -128.25 dBm |
| | | L1c Data code | -133.0 dBm |
| | | P | -133.0 dBm |
| | | M Noise | -128.5 dBm |
| | L2 | L2c or C/A | -136.0 dBm |
| | | P | -136.0 dBm |
| | | M Noise | -132.5 dBm |
| | L5 | I, Q | -127.9 dBm |
| Galileo | E1 | E1-A | -125.5 dBm |
| | | E1-A PRS Noise | -125.5 dBm |
| | | E1-B, E1-C | -128.0 dBm |
| | E6 | E6-A | -125.5 dBm |
| | | E6-A PRS Noise | -125.5 dBm |
| | | E6-B, E6C | -128.0 dBm |
| | E5ab | E5a-I + E5a-Q + E5b-I + E5b-Q | -122.0 dBm |
| GLONASS | L1 | C/A | -131 dBm |
| | | P | -131 dBm |
| | L2 | C/A | -137 dBm |
| | | P | -137 dBm |
| BeiDou | B1 (1.561098 GHz) | B1I | -133 dBm |
| | B1 (1.57542 GHz) | B1C | -130 dBm |
| | B2 (1.20714 GHz) | B2I | -133 dBm |
| | B2 (1.17645 GHz) | B2A | -127 dBm |
| | B3 (1.26852 GHz) | B3I | -133 dBm |
| QZSS | L1 | C/A code | -128.5 dBm |
| | | S | -131 dBm |
| | | L1c Data + Pilot | -127 dBm |
| | L2 | L2c | -130 dBm |
| | L5 | I + Q | -124.9 dBm |
| | L6 | L61/L62 | -126.82 dBm[2] |
| NavIC (IRNSS) | L5 | C/A | -130 dBm |

1 Nominal signal power levels as defined by Spirent. Through SimGEN, the user has extensive facilities to adjust these nominal power levels to meet individual GNSS ICD conditions.
2 Default power level setting is for Block II satellites

**Table 10 Navigation Messages Types per Constellation**

| Constellation | Message Type | Applicable Signal | Requirements | Notes |
|---|---|---|---|---|
| GPS | Legacy | C/A, P, Y | Support for Y code requires SimCLASS/SimSAAS Option | |
| | CNAV | L2c, L5-I | | |
| | CNAV-2 | L1c | | |
| | MNAV | AES-M, M. MNSA | MNSA-M requires SimMNSA option.<br>AES-M requires SimMCODE option.<br>M requires SimMCODE and SDS-M-Code via data server options | |
| Galileo | I/NAV | E1-B, E5b-I | OS Galileo - Excludes SOL support<br>FOC Galileo – Includes SOL support | |
| | F/NAV | E5a-I | OS Galileo - Supported<br>FOC Galileo - Supported | |
| | C/NAV | E6-B | Requires 3rd party PRS[WARE] product | |
| | G/NAV | E1-A, E6-A | Requires 3rd party PRS[WARE] product | |
| GLONASS | Public | L1-C/A | | There is no data message on the GLONASS P-Code |
| BeiDou | D1 and D2 | B1I, B2I | | D2 does not include differential corrections or Iono grid. |
| | | B1C, B2A | | |
| | Legacy | B3I | | |
| SBAS | Data | L1, L5-I | | The same message is broadcast at L1 and L5 for any satellite. |
| QZSS | QZ-Legacy | L1 C/A, L1 SAIF | | |
| | QZ-CNAV | L2c, L5-I | | |
| | QZ-CNAV-2 | L1c | | |
| NavIC | IRNSS legacy | C/A | | |
| FLEX | Standard | All | | See Table 11 |

# Spirent **GSS9000 Series GNSS Simulation System**

**Table 11 FLEX Option Signal Definitions**

| Parameter | Value | Units |
|---|---|---|
| Codes | Three user-definable codes per SV | |
| Code Assignment | +I, -I, +Q, -Q | |
| Code Definition | User-definable memory codes (primary and secondary) | |
| Base Chip Rate | 1.023 | Mcps |
| Chip Rate Multiplier | 1, 2, 2.5, 3, 4, 5, 6, 7, 8, 9, 10 | |
| BOC Rates Multiplier | Integer multiple of Base Chip Rate | |
| Nominal Signal Level | -123 to -133 | dBm |
| Nav Message | Standard for constellation | |

**Table 12 Performance Levels for GSS9000 Series**

| Parameter | Detail | | Value | Foot note |
|---|---|---|---|---|
| RF Signal Level | Carrier Level Control | Maximum | +20 dB | 3 |
| | | Minimum | -40 dB | 4 |
| | | Resolution | 0.1 dB | |
| | | Linearity +20 dB to -30 dB<br>-30.1 dB to -40 dB | <0.10 dB<br><0.20 dB | |
| | Absolute Accuracy<br>Run to Run Repeatability | | ±0.5 dB<br>±0.1 dB | 5 |
| Iteration Rates | Supported SimGEN Simulation Iteration Rates (SIR) | | 10, 100, 250, 500,1000 Hz | |
| | Hardware update rate | | 1000 Hz | |
| Limit of Signal Dynamics | Relative Velocity | | 120,000 m/s | 6 |
| | Relative Acceleration | | 192,600 m/s2 | 7 |
| | Relative Jerk | | 890,400 m/s3 | |
| | Angular Rates (indicative) | (at 1.5 m lever arm)<br>(at 0.05 m lever arm) | >15π rad/s<br>>60π rad/s | |
| Signal Accuracy | Pseudorange Accuracy | | 0.3 mm RMS | 8 |

3 Maximum signal level of +20 dB is available for up to 16 channels per channel bank. A maximum of +17 dB is supported for up to 32 channels per channel bank
4 The control range extends to -50 dB, but performance is unspecified below -40 dB. Operation below -20 dB is primarily to support antenna pattern and multipath functionality.
5 RSS at 21±5°C, +20 to -30 dB. ±1.5 dB 3-sigma, all conditions.
6 For 6-DOF data externally supplied via SimREMOTE or from data file
7 When operating at >=250 Hz SIR
8 For signal acceleration < 450 $m/s^2$, jerk < 500 $m/s^3$, 1000 Hz SIR

| Parameter | Detail | Value | Foot note |
|---|---|---|---|
| | Pseudorange Bias | 0 mm RMS | 9 |
| | Delta-range Accuracy | Better than ±1.0 mm RMS | |
| | Inter-carrier Bias | Better than ±2 ns | 10 |
| | 1PPS to RF Alignment | Better than ±2 ns | 11 |
| Spectral Purity | Harmonics | < -40 dBc | |
| | In-band Spurious | < -182 dBW | 12, 13 |
| | Phase Noise (single sideband) | < 0.005 Rad RMS | 14 |
| Signal Stability | Internal 10.00 MHz OCX Oscillator (after warm up) | ± 5 x 10-10 per day | |
| Static Multipath Channels | Fixed path-length delay per path | 0 to 1245 m | |
| | Resolution (approximately) | 2.4 m | |

**Table 13 GTx Performance**

| Parameter | Detail | Value | Foot Note |
|---|---|---|---|
| Signal sources | Per Frequency Band | 32 | 15 |
| Frequency Bands | | Centre frequency | 16 |
| | GPS L1 | 1.57542 GHz | |
| | GPS L2 | 1.2276 GHz | |
| | GPS L5 | 1.17645 GHz | |
| | Galileo E1 | 1.57542 GHz | |
| | Galileo E5 | 1.191795 GHz | |
| | Galileo E6 | 1.27875 GHz | |
| | GLONASS L1 | 1.602 GHz (F0) | |
| | GLONASS L2 | 1.246 GHz (F0) | |
| | BeiDou B1i | 1.561098 GHz | |
| | BeiDou B2i | 1.20714 GHz | |
| | BeiDou B2a | 1.17645 GHz | |
| | BeiDou B1c | 1.57542 GHz | |
| | BeiDou B3i | 1.26852 GHz | |

9 Single Channel Bank – supporting up to 32 channels. When the same signal is generated across multiple Channel Banks the inter channel bank bias uncertainty is +/-230ps (+/-69mm)
10 Between any RF carrier.
11 Between any RF carrier at the output port(s). Applicable for both single and multi-output systems.
12 For relative velocities <50,000 m/s
13 In-Band Spurious Bandwidths (relative to centre frequency unless otherwise stated):
GPS: L1 ± 20.5 MHz, L2 ± 20.5 MHz, L5 ± 20.5 MHz
Galileo: E1 ± 20 MHz, E6 ± 20 MHz, E5a ± 25.5 MHz, E5b ± 25.5 MHz
GLONASS: (relative to channel frequency 0) L1 ± 20 MHz, L2 ± 20 MHz
BeiDou: B1/B2 ± 20.5 MHz
14 Value is typical, integrated over a 1 Hz to 10 kHz bandwidth. Worst case < 0.01 rad RMS.

[15] For civilian GNSS signals
[16] Subject to licence

# Spirent **GSS9000 Series GNSS Simulation System**

| Parameter | Detail | Value | Foot Note |
|---|---|---|---|
| Carrier frequency offset | Independent for each source | ± 5 MHz | 17 |
| | Resolution | 1 kHz | |
| CW | Power | See 'RF Signal Level' | |
| BPSK | Power | See 'RF Signal Level' | |
| | Main lobe width: Wide Band | 20.46 MHz | |
| | Narrow Band | 0.1023 MHz | |
| CW Pulse | Power | See 'RF Signal Level' | 18 |
| | Pulse width | 1 to 10000 µs | |
| | Pulse repetition interval range | 100 to 10000 µs | |
| | Pulse repetition interval resolution | 100 µs | |
| | Rise time (10% to 90%) | 100 ns (max) | |
| | On/Off ratio min | 30 dB | |
| AWGN | Power | See 'RF Signal Level' | |
| | 3 dB Bandwidth | 0.1, 0.5, 1, 2 10, 20 MHz | |
| | Bandwidth accuracy | ±5% | |
| FM CW | Power | See 'RF Signal Level' | |
| | FM deviation | ±0.01 to ±5 MHz | |
| | FM rate | 0.5 to 10 kHz | |
| | FM rate step size | 0.5 kHz | |
| | Modulating Waveform | Triangular | |
| AM | Power | See 'RF Signal Level' | |
| | Modulation depth | 10 to 90% | |
| | Modulation depth step size | 10% | |
| | AM rate | 0.5 to 10 kHz | |
| | Modulating Waveform | Sinusoidal | |
| PM | Power | See 'RF Signal Level' | |
| | Modulation deviation | ±0 to ±5 rad | |
| | PM rate | 0.5 to 10 kHz | |
| | Modulating Waveform | Sinusoidal | |
| RF Signal Level | Single signal | -47 dBm (max) | 19 |
| | Multiple signals | -72 dBm (max) | 20 |
| | Minimum level per signal | -117 dBm | |
| | Linearity, per signal, >-97 dBm | <0.1 dB | |
| | Linearity: per signal, > –107 dBm | <0.2 dB | |
| | Linearity: per signal, > –117 dBm | <0.5 dB | |

[17] In addition to Doppler caused by vehicle motion. Applies to all signal types
[18] At 100% duty cycle. Average power reduces in proportion to duty cycle.
[19] Single signal per channel bank (CW, FM, PM), -49dBm (BPSK, pulsed CW), -53dBm (AM), -60dBm (AWGN).
[20] Per signal, up to 16 signals of AWGN on the same channel bank – other signal types can be up to 3dB higher

| Parameter | Detail | Value | Foot Note |
|---|---|---|---|

# Spirent **GSS9000 Series GNSS Simulation System**

## Performance in multi-chassis configurations

There is a practical limit to how much data can be reliably processed by the simulation engine at the designated simulation iteration rate. There are many factors that can influence the processing capacity of the simulation system, but in practical terms the main sources are:

- The total number of active channel banks (influenced by the number of antenna outputs in the configuration and the selected signal types)
- The total number of satellite signals (channel density)
- The volume of data logging enabled and the logging rate

The variety of permutations from these contributing factors is extremely difficult to fully characterise. Instead Spirent provides guidance based on previously explored cases in order to set a reasonable expectation of the performance that can be achieved.

For a system with a capability of 256 channels or greater:

- The simulation iteration rate shall be 100Hz
- SimGEN ‘truth’ data logging capability, during real-time scenario playback, must be limited to bulk logging in binary format OR data-streaming UDP output OR nav data binary dump.
- To access scenario ‘truth’ data from any other source, or to employ two or more sources concurrently, SimGEN should be run in ‘no hardware mode’.

For a system with more than 256 channels, up to and including 512 channels:

- It will be necessary to strike a balance between the increasing channel density and truth data output by:
    - Decreasing the real-time data logging rate; or
    - Needing to rely solely on UDP data-streaming; or
    - Having to disable real-time logging and rely solely on ‘no hardware mode’ pre/post-processing data capture.

If these operating criteria present a challenge to the intended test application, and for systems of more than 512 channels, Spirent is pleased to discuss the challenges of each user case and to determine whether an alternative system architecture might be suitable in those circumstances, via a Tailored Solution.

## Table 14 Signal Generator Connectivity

| Port | Type | Parameter |
|---|---|---|
| Main RF Port | Output | N-type coax female, 50 Ω, VSWR <1.2:1<br>AC coupled ±50 V DC, maximum reverse RF 30 dBm |
| High Level RF Port | Output | N-type coax female, 50 Ω, VSWR <1.2:1<br>AC coupled ±50 V DC, maximum reverse RF 30 dBm |
| Individual RF Ports | Output | N-type coax female, 50 Ω, VSWR <1.2:1<br>AC coupled ±50 V DC, maximum reverse RF 30 dBm |
| Auxiliary RF | Input | N-type coax female, 50 Ω, VSWR <1.4:1<br>0.5 to 2 GHz, Insertion Loss 14.5 dB typical |
| External Frequency Standard | Input | BNC coax socket, 50 Ω<br>-5 to +10 dBm at 1 MHz, 5 MHz, 10 MHz |
| Internal Frequency Standard | Output | BNC coax socket, 50 Ω<br>10.00 MHz at +5 dBm nominal |
| 1PPS IN | Input | BNC coax socket, 50 Ω, TTL level compatible |
| 1PPS OUT | Output | BNC coax socket, 50 Ω, TTL level compatible |
| Trigger IN | Input | BNC coax socket, 50 Ω, TTL level compatible |
| PCI Express | Private Bus | Cabled PCIe |

## Table 15 C50r SimGEN Host Connectivity

| Interface | Type | Parameter |
|---|---|---|
| PCI Express | Private Bus | Cabled PCIe |
| USB | I/O | Maximum of 4 spare ports for general file access |
| Ethernet | I/O | RJ-45 Ethernet interface standard. Used for general network access and available for remote control |
| Optional GPIB | I/O | Available for remote control and GSS7765 control |
| Optional ScramNET | I/O | Available for remote control |

# Spirent **GSS9000 Series GNSS Simulation System**

**Table 16 Physical and Environmental Properties**

| Part | Parameter | Value |
|---|---|---|
| Signal Generator | Approximate Dimensions (H x W x D) (19” 4U chassis) | 175 mm x 445 mm x 620 mm<br>6.9” x 17.75” x 24” |
| | Typical Weight | <30 kg (66 lb) (configuration dependent) |
| | Operating Environment | +10 to +40°C (50 to 104°F) (40-90% RH, non-condensing) |
| | Storage Environment | -40 to +60°C (-90 to 140°F) (20-90% RH, non-condensing) |
| | Electrical Power | 100-120 V 220-240 V<br>4.0 A 2.0 A<br>48 to 66 Hz 48 to 66 Hz |
| Standard C50r SimGEN Host | Approximate Dimensions (H x W x D) (19” 4U chassis) | 177.8 mm x 426.0 mm (482.0 mm with Rack Mount installed) x 600.6 mm (Not including front handles and front bezel door closed)<br>7.00” x 16.77” (18.98”) x 23.65” |
| | Weight (excl. peripherals) | <20 kg (44 lb) |
| System Mean Time Between (component) Failure (MTBF) | 2,562,327 | Hours (per Bellcore 6) |

**Table 17 Safety and EMC Compliance**

| Compliance | Applicable Standard |
|---|---|
| Safety | Low Voltage Directive (LVD) 2006/95/EC<br>BS EN 60950-1:2006 Information technology equipment. Safety. General requirements |
| EMC | EMC Directive 2004/108/EC<br>EN 61326-1:2006 Electrical equipment for measurement, control and laboratory use. EMC requirements. General requirements |

# Related Brochures, Data Sheets and Specifications

**Table 18 Related Product References**

| Related Product | Description | Data Sheet / Specification |
|---|---|---|
| SimGEN | GNSS Software Suite | MS3008 |
| SimINERTIAL | Inertial Sensor Emulation Option | MS3030 |
| SimBARO | Barometric Pressure Emulation Option | MS3056 |
| SimAUTO | Automotive Sensor Emulation Option<br>Single Axis Rate Table Option | MS3023<br>MS3049 |
| SimCS | Galileo FOC Upgrade Option | MS9043 |
| SimCLASS | GPS SA/A-S Upgrade Option (Non-USA) | MS9020 |
| SimSAAS | GPS SA/A-S Upgrade Option (USA only) | SF1001 |
| SimMNSA<br>SimMCODE<br>SDS-M-Code | MNSA M-code Upgrade Option<br>AES M-Code Upgrade Option<br>SDS-M-Code via server Upgrade to SimMCODE | MS9018<br>MS9048 |
| SimSAFE | Vulnerability Test Tool | MS3092 |
| SimREMOTE | Simulator Remote Control Additional Options | MS3015 |
| GBAS | GSS4150 VHF Data Broadcast Simulator for GBAS Product Specification | MS3014 |
| GSS7765 | Generic Interference Generator Option | MS3055 |
| SimSENSOR | MEMS Sensor Simulation Option | MS3086 |
| SimROUTE | Road-Matched Trajectory generation Tool | MS3073 |

# Spirent **GSS9000 Series GNSS Simulation System**

## ICD Compliance – Applicable Documents

**Table 19 ICD compliance[21] (WORK IN PROGRESS)**

| Reference | | Title | Issue | Notes |
|---|---|---|---|---|
| GPS | IS-GPS-200 | NAVSTAR GPS Space Segment/Navigation User Segment Interfaces | K | |
| | IS-GPS-705 | NAVSTAR GPS Space Segment/User Segment L5 Interfaces | F | |
| | IS-GPS-800 | NAVSTAR GPS Space Segment/User Segment L1C Interfaces | F | |
| GLONASS | ICD L1, L2 GLONASS | GLONASS Interface Control Document, Navigational radiosignal in bands L1, L2 | 5.1(2) | |
| Galileo | OS SIS ICD | European GNSS (Galileo) Open Service, Signal-in-Space Interface Control Document | 1.3 | |
| | FOC SIS ICD | FOC Galileo Signal-in-Space Interface Control Document GAL-ICD-ESA-SYST-X/0027 | 1.2 | |
| QZSS | IS-QZSS-PNT-001 | Quasi-Zenith Satellite System Interface Specification Satellite Positioning, Navigation and Timing Service | 003 | L1, L2, L5 |
| | IS-QZSS-L6-001 | Quasi-Zenith Satellite System Interface Specification Centimetre Level Augmentation Service | Draft Edition, Apr 2018 | L6 |
| | IS-QZSS-L1S-003 | Quasi-Zenith Satellite System Interface Specification Sub-meter Level Augmentation Service | 003 | |
| | IS-QZSS-TV | - | 002 | L5S |
| Beidou | BDS-SIS-ICD (B2I) | BeiDou Navigation Satellite System (Phase-2) Signal-in-Space Interface Control Document Open Service Signal | 2.1 | B2I |
| | BDS-SIS-ICD (B1C, B2a) | BeiDou Navigation Satellite System (Phase-3) Signal-in-Space Interface Control Document Open Service Signals | 1.0 | B1C, B2a |
| | BDS_SIS-ICD-B3I | BeiDou Navigation Satellite System Signal-in-Space Interface Control Document Open Service Signals B3I | 1.0 | |
| SBAS | RTCA DO-229 | SBAS MOPS | D | |
| LAAS | RTCA DO-246 | | C | Partial support for Rev. D |
| | NMEA | 0183 | 4.10 | |
| IRNSS | IRNSS_SISICD_SPS | ISRO-ISAC-IRNSS-PR July 2011 IRNSS Signal-in-Space ICD for SPS | 1.1 | |
| | RINEX | - | 3.00 | |

Spirent operates a policy of upgrades to meet ICD changes as they are adopted. To obtain ongoing upgrades your system needs to be under warranty or a current support agreement.

Please contact Spirent for current ICD compliance, including for information relating to export-controlled options and those for authorised users that are not shown here.

[21] Compliance assumes the latest version of SimGEN™ is installed and is being used on the C50r

## Glossary of terms

| | |
|---|---|
| 1PPS | One Pulse-Per-Second |
| BITE | Built In Test Equipment |
| AOC | Auxiliary Output Chip |
| BOC | Binary Offset Carrier |
| BeiDou | Chinese GNSS System |
| CS | Commercial Service - Galileo |
| DOP | Dilution Of Precision caused by satellite geometry |
| EMC | Electromagnetic Compatibility |
| FLEX | Flexible constellation with user defined code and BOC rates |
| FPGA | Field-Programmable Gate Array – a reconfigurable electronic device |
| FOC | Full Operational Capability – available to authorised Galileo customers via SimCS |
| GALILEO | EU GNSS System |
| GPS | Global Positioning System US GNSS system |
| GNSS | Global Navigation Satellite System (Galileo +GPS+SBAS+GLONASS+IRNSS+BeiDou) |
| GLONASS | GLObal NAvigation Satellite System (Russian Federation) |
| GTx | Ground Transmitters – Embedded interference generation |
| GUI | Graphical User Interface |
| HUR | Hardware Update Rate |
| IRNSS | Indian Regional Navigation Satellite System |
| ICD | Interface Control Document |
| IEEE-488 | An 8-bit parallel Hardware Interface |
| MTBF | Mean Time Between Failure |
| NavIC | Navigation with Indian Constellation |
| OS | Open Service – Galileo |
| PRS | Public Regulated Service -Galileo |
| PRS-NOISE | A signal with the same spectral distribution as PRS, but with an arbitrary code structure of the correct chip rate that is phase and frequency correlated with the other Galileo signals |
| PRN | Pseudo-Random Number, representing the unique transmitted signal code |
| QZSS | Quasi-Zenith Satellite System |
| RAIM | Receiver Autonomous Integrity Monitoring |
| RF | Radio Frequency |
| SBAS | Space-Based Augmentation System (such as WAAS, EGNOS, MSAS) |
| SDS | SDS-M-Code via data server |
| SOL | Safety Of Life |
| SIR | Simulation Iteration Rate |

# Spirent **GSS9000 Series GNSS Simulation System**

## For more information

For more information on any aspect of the GSS9000, please contact your Spirent representative or Spirent directly:

**Spirent Communications plc**

Address: Aspen Way, Paignton, Devon TQ4 7QR, UK

Telephone: +44 1803 546325

E-mail: globalsales@spirent.com

Website: www.spirent.com

**US Government & Defence, Spirent Federal Systems Inc,**

Address: 1402 W. State Road, Pleasant Grove, UT 84062

Telephone: +1 801 785 1448

E-mail: info@spirentfederal.com

Website: www.spirentfederal.com

spirent.com

Spirent Communications plc, Aspen Way, Paignton, Devon TQ4 7QR, UK
Tel +44 (0)1803 546300 Fax +44 (0)1803 546301
www.spirent.com/positioning
Registered in England Number 00470893
Registered office: Origin One, 108 High Street, Crawley, West Sussex RH10 1BD, UK
Tel: +44 (0)1293 767676, Fax: +44 (0)1293 767677

© 2020 Spirent. All Rights Reserved.
All of the company names and/or brand names and/or product names referred to in this document, in particular, the name “Spirent” and its logo device, are either registered trademarks or trademarks of Spirent plc and its subsidiaries, pending registration in accordance with relevant national laws.

All other registered trademarks or trademarks are the property of their respective owners.

The information contained in this document is subject to change without notice and does not represent a commitment on the part of Spirent. The information in this document
is believed to be accurate and reliable; however, Spirent assumes no responsibility or liability for any errors or inaccuracies that may appear in the document.